

378

SUBDIVISION OF T. 32 N., R. 31 E.

Chains

- 54.80 N. end of rocky spur, slopes N.
- 56.60 Main dry wash, 10 lks. wide, course S.E.
- 62.10 Main dry wash, 10 lks. wide, course N.E.
- 68.60 Main dry wash, 10 lks. wide, course S.E.
- 73.20 Road, bears N.W. and S.E.
- 74.60 Another dry wash, 3 lks. wide, course S.E.
- 80.10 The cor. of secs. 2, 3, 10 and 11.

Land mountainous.

Soil, mostly sand and clay mixed with some loam; 2nd. rate.

No timber; desert brush.

Mountainous land 80.00 chs.

From the cor. of secs. 2, 3, 10 and 11, the mouth of a tunnel of copper mine bears N.15°25'E., 54.00 chs.

A small spring of pure water bears S. 57°45'E., 32 chs.; thence, I run from said cor.


N.0°03'E., on a true line bet. secs. 2 and 3.

Ascend S. slope of mountain.

29.70 Point, whence, a shaft 20 ft deep, bears W. 10 lks.

31.00 Top of rocky spur, slopes S.W. Continue to ascend very steep S.W. slope/

40.00 Set an iron post, 3 ft. long, 1 in. dia., 24 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.;



and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

47.00 Top of spur, slopes S.W. Continue over slide rock, along W. slope of high rocky mountain.

69.00 Cross head of draw, course W.

78.93 Intersect the N.bdy. of Tp. 8.20. chs. N.89°55'E. of 1/4 cor. for sec. 34 and 32.67 chs. S.89°55'W. of the point for cor. of secs. 34 and 35.

at the point of intersection I

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for closing cor. of secs. 2 and 3, with brass