

Subdivision of T. 25 N., R. 32 E.

Chains

West on a true line bet. secs. 29 and 32.

Over level desert land covered with scattering greasewood.

29.20 Top of low ridge, bears N. and S., desc. over rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. with a brass cap, marked $\frac{1}{4}$ S 29

S 32

1912

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.59.00 Dry wash, 5 lks. wide, course S. 10° E.68.10 Dry wash, 10 lks. wide, course S. 20° W.

75.00 Dry wash, 5 lks. wide, course SE.

80.00 Cor. of secs. 29, 30, 31 and 32.

Surface level and rolling.

Soil sandy and gravelly, 3rd. rate.

Undergrowth scattering greasewood.

Drains S.

West on a true line bet. secs. 30 and 31.

Over rolling land covered with scattering greasewood.

9.20 Dry wash, 5 lks. wide, course S. 30° E.24.00 Dry wash, 75 lks. wide, course S. 20° E.

39.00 Dry wash, 10 lks. wide, course S.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with a brass cap, marked $\frac{1}{4}$ S 30

S 31

1912

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.56.50 Wagon road, bears S. 20° E., and N. 20° W.85.61 Intersect W. bdy. of township 4.20 chs. N. 0° $30'$ E. of