

Subdivision of T. 25 N., R. 32 E.

Chains

- 43.50 Top of N. slope of spur, bears N. and S., desc.
- 55.00 Dry wash in gully, 10 lks. wide, course S. 10° E., asc.
- 63.00 Top of ridge, bears S. 20° W. and N. 20° E., desc.
- 66.50 Dry wash, in canon, 40 lks. wide, course S. 30° W., asc.
- 72.30 Top of N. slope of spur, bears N. and S., desc.
- 80.20 Cor. of secs. 17, 18, 19 and 20.

Surface rough mountainous.

Soil stony, 4th. rate.

No undergrowth.

Drains S.

Mountainous land 80.20 chs.

West on a true line bet. secs. 18 and 19.

Desc. over rough mountainous land.

- 4.50 Gully, 10 lks. wide, course SW., asc.
- 26.00 Top of main mountain range, bears NE. and SW., desc.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in the ground to bedrock, in a mound of stone for $\frac{1}{4}$ sec. cor., with a brass cap, marked

$\frac{1}{4}$ S 18 ✓

 S 19
 1912

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

- 44.50 Gully, 10 lks. wide, course N. 20° W., asc.
- 52.00 Top of spur, bears N. 20° W., and S. 20° E., desc.
- 59.00 Dry wash in gully, 10 lks. wide, course N., asc.
- 70.00 Dry wash in canon, 30 lks. wide, course N. 25° W., asc.
- 79.00 Top of spur, bears NW. and SE., desc.
- 83.93 Intersect W. bdy. of township 4.20 chs. N. 1° 56' E. of the cor. of secs. 13 and 24.
Set an iron post 3 ft. long, 2 ins. in diam., 18 ins. in the ground to bedrock, in a mound of stone for closing cor. of secs. 18 and 19, with a brass cap, marked