

Subdivision of fract. T. 26 N., R. 32 E.

Chains

58.00 Top of ridge, bears N. 10° E. and S. 10° W., desc.

79.60 Gully, 15 lks. wide, course S. 30° W., asc.

80.09 Cor. of secs. 23, 24, 25 and 26.

Surface rough mountainous.

No soil, barren rocks.

No undergrowth.

Drains west.

Mountainous land 80.09 chs.

East on a true line bet. secs. 24 and 25.

Asc. over rough mountainous land.

5.00 Top of S. slope of spur, bears SW., desc.

14.10 Gully, 10 lks. wide, course SW., asc.

23.50 Top of main mt. range, 6000 ft. alt., bears N. and S., desc.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in the ground to bedrock, in a mound of stone for $\frac{1}{4}$ sec. cor., with a brass cap, marked

$\frac{1}{4}$ S 24

S 25

1912

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor..

40.10 Gully, 10 lks. wide, course SE., asc.

60.00 Top of ridge, bears NE. and SW., desc.

65.80 Gully, 10 lks. wide, course SW., asc. abruptly.

71.50 Top of high ridge, bears S. 60° E. and N. 60° W., desc.
 $0^{\circ}4'$ W.

76.78 Intersect E. bdy. of tp. 1.40 chs. S. of the cor. of secs. 19 and 30.

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for closing cor. of secs. 24 and 25, with a brass cap, marked

