

Subdivision of fracl. T. 26 N., R. 32 E.

Chains

64.20 Wagon road, bears E. and W.

65.00 Leave canon, asc.

75.00 Top of W. slope of spur, bears S. 75°W., desc.

80.00 Intersect N. bdy. of Tp. 3.00 chs. S. 89° 40' E. of the
cor. of secs. 35 and 36.

Set an iron post, 3 ft. long, 2 ins. in diam. 24 ins. in
the ground for closing cor. of secs. 1 and 2, with
a brass cap, marked

T 27 N		R 32 E
S 35		S 36
	cc	
S 2		S 1
T 26 N		R 32 E

1912

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high S. of
cor.

Surface rough mountainous.

No soil, barren rocks.

No undergrowth.

Drains W.

Mountainous land 80.00 chs.

Oct. 20, 1912.

Beginning at the closing cor. of secs. 1 and 2 on N. bdy.
of Tp., I run

N. 89° 40' W. on a blank line along the N. Bdy. sec. 2.

3.00 Intersect cor. of secs. 35 and 36. Thence N. 89° 52' W. to

40.20 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in
the ground for $\frac{1}{4}$ cor. of sec. 2, with a brass cap,
marked

 $\frac{1}{4}$ S 2

1912

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of
cor.

Beginning at the closing cor. of secs. 1 and 12 on the E.
bdy. of the Tp., I run

S. 0° 4' W. on a blank line along the E. bdy. of sec. 12