

200

Subdivision of fractl. T. 30 N., R 32 E

Chains.	
42.00	Wash, 10 lbs. wide course 560°E ; asc.
52.00	Top of spur, bearing 520°E . and N. 20°W . descended.
70.50	Wash, 10 lbs. wide, course 570°E ; desc.
79.80	The cor. of secs. 9, 10, 15 and 16 Land, mountainous and rolling. Soil, stony; 2nd and 3rd rate undergrowth, sage and desert brush No timber Mountainous land, 24.00 Chains. Oct. 1,

Oct. 2.

From the cor. of secs. 3, 4, 9 and 10
I run North on a true line
bet. secs. 3 and 4.

Over rolling land, descending

22.50	Wash, 20 lbs. wide course 580°E
-------	---

36.50	Wash, 15 lbs. wide, course East
-------	---------------------------------

40.00	Set an iron post 3 ft. long, 1 in. diam., 24 ins. in the ground for $\frac{1}{4}$ cor. of secs. 3 and 4 with brass cap mkd;
-------	--

$54\frac{1}{4}$ | 53
 ✓

1912

and raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

42.50	Wash, 10 lbs. wide, course East.
-------	----------------------------------

57.40	Wash, 20 lbs. wide, course 575°E .
-------	--

68.80	Wash, 10 lbs. wide, course East.
-------	----------------------------------

79.63	Intersect the sixth standard parallel, 79 lbs. $589^{\circ} 49' \text{W}$. of the standard cor. of secs. 33 and 34, T 31 N., R 32 E., which is a lava rock $6 \times 8 \times 4$ ins. above ground, mkd. and witnessed as described by the Surveyor General. At the point of intersection I build a cor. as follows:
-------	---

Set an iron post 3 ft. long,
2 ins. diam., 24 ins. in the