


Subdivision of T. 25 N., R. 33 E.

Chains

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with a brass cap, marked




Dig pits 18 X 18 X 12 ins. E. and W. of post, 3 ft. dist. and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

50.00 Dry wash, 10 lks. wide, course S. 60 W.

87.65 Intersect E. bdy. township 5.54 chs. N. $0^{\circ} 13'$ W. of the cor. of secs. 30 and 31, T. 25 N., R. 34 E.

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for closing cor. of secs. 25 and 30, with a brass cap, marked



Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. cor.

Surface level.

Soil sandy and gravelly, 3rd. rate.

Undergrowth, scattering greasewood.


Drains SW.

N. $0^{\circ} 1'$ W. bet. secs. 25 and 26.

Over level land covered with scattering greasewood.

33.20 Dry wash, 10 lks. wide, course S. 60° W.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with a brass cap, marked



Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.