Chains

80.12 Old cor. of secs. 2, 3, 10 and 11, bears W. 10 lks., a limestone 20x12x8 ins. above ground, marked with 5 notches on S. and 2 notches on E. edge, with a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Course of last $\frac{1}{2}$ mile is N.0°04'W.

From the cor. of secs. 2, 3, 10 and 11, above described, I retrace

East bet. secs. 2 and 11.

30.00 After diligent search, I failed to find any trace of old fractional cor. of secs. 2 and 11.

From the same cor. of secs. 2, 3, 10 and 11, I retrace North bet. secs. 2 and 3.

- 40.06 Old $\frac{1}{4}$ sec. cor. bears W. 2 lks.; a limestone 20x12x10 ins. above ground, firmly set, marked $\frac{1}{4}$ on the W. face with a mound of stone 2 ft. base, $l\frac{1}{2}$ ft. high, W. of cor. Course of $\frac{1}{2}$ mile is N.0°02'W.
- Intersect the N. Bdy. of the Tp. 5 lks. E. of the cor. of secs. 2, 3, 34 and 35; a quartzite rock 15x10x6 ins. above ground, firmly set and marked with 2 grooves on the E. and 4 grooves on the W. face, with a mound of stone 2 ft. base, 1½ ft. high, N. of cor. Course of last ½ mile is N.0°03*W.

RETRACEMENT OF THE N. BDY. of T.30 N.R.33 E.

From the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of Tp. above described, I retrace
N.88°15'E. (the course given by the Surveyor general) on
N. bdy. of sec.2.

- 39.91 Old $\frac{1}{4}$ sec. cor. bears S.120 lks.; a slate rock 24x18x5 ins. firmly set in a mound of stone, marked and witnessed as described by the Surveyor General.
 - Course of $\frac{1}{2}$ mile is N.89°57'E., 39.89 chs.
- 79.73 Old cor. of secs. 1, 2, 35 and 36, bears S. 238 lks.; a limestone 12x10x8 ins. above ground, firmly set, and