

SUBDIVISION OF T. 30 N., R. 33 E.

Chains

To complete the survey of sec. 27, I proceed as follows:-
 From the cor. of secs. 27, 28, 33 and 34, heretofore described, I run East, 80.63 chs., ~~a point due South~~
 of the $\frac{1}{4}$ Sec. Cor. of Secs. 26 & 27; thence, I run
 North, and at 40.00 chs. I intersect the $\frac{1}{4}$ sec. cor.
 of secs. 26 and 27. I then return to the cor. of
 secs. 27, 28, 33 and 34, and run
 East on a true line, bet. secs. 27 and 34.

Over rolling land. Ascend.

- 1.50 Road, bears N.N.E. and S.S.W.
 2.00 Wire fence, bears N.W. and S.E. At 1 ch. N.W. fence
 turns W.
 11.00 Dry wash, 20 lks. wide, course W.N.W.
 25.75 Point, whence, forks of dry wash, bears S. 1 ch., course
 W.S.W. and N.W.
 27.00 Small drywash, 10 lks. wide, course, W.S.W.
 40.74 Point due south of the $\frac{1}{4}$ sec. cor. on the N. bdy. of
 sec. 27. I therefore at this point
 Set an iron post, 3 ft long, 1 in. dia., 24 ins. in the
 ground, for $\frac{1}{4}$ sec cor., with brass cap mkd.;

$$\begin{array}{r} \frac{1}{4} \text{ S } 27 \\ \hline \text{S } 34 \\ 1912; \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 N. of cor.

- 57.00 Draw, course N.W. Joins big gulch 10 chs. N.W. Ascend
 steep.
 75.00 Top of steep ascent. Continue to ascend less steeply.
 80.63 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in
 the ground, for cor. of secs. 26, 27, 34 and 35,
 with brass cap mkd.;

$$\begin{array}{r} \text{T } 30 \text{ N } \quad \text{R } 33 \text{ E} \\ \text{S } 27 \quad | \quad \text{S } 26 \\ \hline \text{S } 34 \quad | \quad \text{S } 35 \\ 1912; \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.

Land part rolling, part mountainous.