

## Resurvey of the S. Bdy. of T. 32 N., R. 34 E.

Chains

- 58.70 Top of spur, bears NW. and SE., desc.
- 78.75 Intersect old standard cor. of secs. 35 and 36. I destroy the markings on stone at this cor., and remark same A P for angle point.
- Thence I run
- S. 89° 59' E. bet. secs. 1 and 35, and at
- 80.00 Set an iron post, 3 ft. long, 3 ins. in diam., 24 ins. in the ground for standard cor. of secs. 35 and 36, with a brass cap, marked

T 32 N	R 34 E
S 35	S 36 ✓
S C	

1913

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Land mountainous.

Soil sandy loam and stony, 3rd. and 4th. rate.

Undergrowth scattering sage-brush and small junipers

No timber.

Drains SE.

Mountainous land 80.00 chs.

S. 89° 59' E. on a true line bet. secs. 1 and 36.

Desc. over rolling and level land.

- 11.70 Intersect the closing cor. of secs. 1 and 6.
- 39.31 Intersect the old ¼ standard cor. of sec. 36.
- I destroy all trace of this cor., and at
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for a new ¼ sec. cor., with a brass cap, marked

S ¼	36
-----	----

S C

1913

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.