

Resurvey of the subdivisions of T. 32 N., R. 34 E.

Chains	Land level and rolling. Soil sandy loam and gravelly, 3rd. rate. Undergrowth scattering sage-brush. Drains N.

	Beginning at the cor. of secs. 14, 15, 22 and 23, I run S. 1° 53' W. on a true line on the N. half mile bet. secs. 22 and 23. Over level land.
8.30	Dry wash, 12 lks. wide, 4 ft. deep, course N. 25° E.
27.10	Dry wash, 12 lks. wide, 3 ft. deep, course N. 15° E.
40.38	$\frac{1}{4}$ sec. cor. Land level. Soil sandy loam, 3rd. rate. Undergrowth scattering sage-brush. Drains West.
	Aug. 7, 1914.

	Subdivision of Fracl. T. 32 N., R. 34 E.
	June 20, 1913. Beginning at the $\frac{1}{4}$ cor. bet. secs. 13 and 24, I run East on a true line on the E. half mile bet. secs. 13 and 24. Asc. over rolling mountainous land.
2.80	Top of spur, bears N. 5° E. and S. 5° W., desc.
7.20	Dry wash, 20 lks. wide, course N., asc.
23.00	Top of ridge, bears N. and S., desc.
35.00	Gulch 20 lks. wide, course N. 65° E., asc.
38.40	Spur, bears N. 60° E., desc.
53.50	Old road, bears N. and S.
59.70	Dry wash, 10 lks. wide, course N. 30° E.
60.33	Intersect the E. bdy. of the township 18.64 chs. S. 0° 26' E. of the $\frac{1}{4}$ cor. on the W. bdy. of sec. 20, T.32 N., R.35 E. Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for closing cor. of secs. 13 and 24, with a brass cap, marked