

Retracement of West Bdy. of T26 N. R 36 E.

chains

described by the surveyor general;  
the line bears  $50^{\circ}10'E$ .

May-10-1913

Subdivision of T26 N., R35 E.


May-13-1913; At 8 am. 1. mt. I set off  
 $40^{\circ}09'N$  on the lat. arc;  $18^{\circ}21\frac{1}{2}'N$ , on  
the decl. arc; and determine a  
meridian with the solar at the  
corner of secs. 5, 6, 31 and 32, <sup>on N Bdy of Townships</sup> which  
is an iron post, heretofore described.

Thence I run

$50^{\circ}W$  bet. secs. 5 and 6.

Over slightly rolling ground through  
sage brush, and over lava rocks.

- 5.70 Enter wash, 10 lbs. wide, course  $56^{\circ}E$ .
- 28.90 Enter wash, 50 lbs. wide, course  $N 50^{\circ}E$ .
- 40.00 Set an iron post, 3 ft. long, lin.  
in diam., 18 ins. in ground, for  
 $\frac{1}{4}$  corner to secs 5 and 6, with  
brass cap, marked.



build mound of stone, 2 ft. base,  
 $1\frac{1}{2}$  ft. high, W. of cor. also build mound  
of stones around iron post. Pits im-  
practicable.

- 46.10 Enter wash, 30 lbs. wide, course  $N 80^{\circ}E$ .
- 53.80 Enter wash 100 lbs. wide, course  $N 70^{\circ}E$ .
- 62.70 Enter wash 50 lbs wide, course East.
- 74.60 Road, bears  $565^{\circ}W$  and  $N 65^{\circ}E$ .
- 75.70 Road, bears  $540^{\circ}W$  and  $N 40^{\circ}E$ .
- 80.00 Set an iron post, 3 ft long, 2 ins.  
in diam., 24 ins in the ground for  
corner to secs. 5, 6, 7 and 8, with  
brass cap, marked.

