

Subdivision of T27N, R35E.

chains Surveyed by Thos A Haigh.

Thence from  
 $N89^{\circ}48'W$ , on a true line bet.  
 secs. 19 and 30.  
 Ascend N.E. slope. through sage  
 brush.

4.80 Top of spur, bears  $N60^{\circ}W$ , and  $S60^{\circ}E$ .  
 Descend S.W. slope

11.10 Enter wash, 30 lks. wide, 6 ft deep,  
 course S.  
 Descend western slope

21.50 Enter wash, 50 lks. wide, 10 ft deep.  
 course  $S65^{\circ}E$ .  
 Ascend steep eastern slope.

40.00 Set iron post, 3 ft. long, 1 in.  
 in diam, 24 ins. in ground,  
 for  $\frac{1}{4}$  sec. cor., with brass  
 cap. marked,

$$\begin{array}{r} 519 \\ \frac{1}{4} \\ \hline 530 \\ 1913 \end{array}$$

raise a mound of stones, 2 ft.  
 base,  $1\frac{1}{2}$  ft. high, N. of cor. Pits  
 impracticable.

42.00 Over granite cropping.

47.10 Top of ridge, bears  $S60^{\circ}E$  and  
 $N60^{\circ}W$ , Descend S.W. slope

51.30 Enter wash 15 lks wide 4 ft. deep.  
 course  $S10^{\circ}E$ .

63.00 Enter wash, 20 lks wide, 6 ft. deep.  
 course  $S40^{\circ}E$ , ascend along northern  
 slope

77.80 Top of ridge, bears  $N80^{\circ}E$ , and  $S80^{\circ}W$ .  
 Descend steep slope

85.90 Intersect, the W. bdy. of Tp. 146 chs  
 $N0^{\circ}08'W$  of cor. of secs. 24 and 25, which  
 is a stone corner heretofore described.  
 Set iron post 3 ft. long 2 in.  
 in diam, 24 ins. in ground, for  
 closing cor. of secs 19 and 30.,  
 with brass cap marked.