

Subdivision of T27N, R35E.

Chains.	
.50	Gulch, from W. to point 75 lbs N.
	thence S.; ascend steep rocky slope through scattering junipers.
21.50	Sulch., course, N60°E., same gulch.
	ascend steep slope.
40.00	Set iron post 3 ft long, 1 in.
	in diam., 2 ins. to bed rock,
	in mound of stone, for $\frac{1}{4}$
	sec. cor., with brass cap, marked,
	$\begin{array}{r} 56 \\ \frac{1}{4} \\ \hline 57 \\ 1913 \end{array}$
	raise a mound of stone, 2 ft.
	base, $1\frac{1}{2}$ ft. high, S. of cor.
	Built S. of cor. to insure safety.
	Point N. of cor. comes on narrow
	rocky cliff. Pits impracticable.
41.00	High ridge, 800 ft. high, bears
	NE. and SW.; descend;
41.50	Descend over cliffs, 50 ft., bears
	NE. and SW.
49.00	Gulch, course, N30°E.; ascend.
55.00	Top of spur, bears N and S; descend
	slightly along N. slope.
60.00	Top of spur, bears NW. and SE.;
	descend steep slopes.
78.50	Big ravine, 200 ft deep, 4 ch. wide,
	course, N.; ascend steep slope.
86.09	Intersect W. bdy. of T <sub>66</sub> lbs.
	N0°02'E. of cor. of secs. 1 and 12.
	which is a rock, heretofore de-
	scribed.
	Set an iron post 3 ft long,
	2 ins. in diam., 12. ins. in
	ground, to bed rock, in mound
	of stone, for closing cor. of
	secs. 6 and 7, with brass
	cap, marked,