


Retracement of S. bdy. of T. 32 N., R. 36 E.

Chains June 26, 1913. *Surveyed by Thos A Haigh*

The cor. of secs. 1, 2, 35 and 36 on the S. bdy. of T. 32 N., R. 36 E. is a trace of a mound and pits with a decayed stake set in the SW. pit. As this cor. is practically obliterated I destroy all trace and at same point

Set an iron post, 3 ft. long, 3 ins. in diam., 24 ins. in the ground for a new sec. cor., with a brass cap, marked

T 32 N R 36 E



T 31 N

1913

Dig pits 18 X 18 X 12 ins. in each sec., 5½ ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

At 8h., a. m., 1. m. t., I set off 23° 23½' N. on the decl. arc, and 40° 35' N. on the lat. arc, and determine a meridian with the solar:

Thence I retrace

East on a random line bet. secs. 1 and 36.

40.00 Intersect a point 40 lks N. of the ¼ sec. cor., which is a granite stone, 10 X 12 X 7 ins. above ground, marked and witnessed as described by the surveyor general.

Course of this half mile is S. 89° 25' E.

I continue line east and at

77.60 Intersect the E. bdy. of the township 36 lks. N. of the cor. of Tps. 31 and 32 N., Rs. 36 and 37 E., which is a redwood post, 3 X 3 ins., 36 ins. long, marked as described by the surveyor general and set in a stone mound.

I destroy all trace of the old cor. and at same point

Set an iron post, 3 ft. long, 3 ins. in diam., 24 ins. in the ground for a new cor. for Tps. 31 and 32 N., Rs. 36 and 37 E., with a brass cap, marked