

## Resurvey of Subdivision of T. 32 N., R. 37 E.

Chains

T 32 N R 37 E

S 3

S 10

1913

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

17.20 Dry wash, 20 lks. wide, 2 ft. deep, course E.

33.10 Dry wash, 30 lks. wide, 3 ft. deep, course N.  $70^{\circ}$  E.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for  $\frac{1}{4}$  cor. for sec. 2, with a brass cap, marked

|  
 $\frac{1}{4}$  S 2  
1913

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.

dist., and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft.

high, E. of cor.

41.21 The true point for  $\frac{1}{4}$  sec. cor. for sec. 2 only.

44.40 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for  $\frac{1}{4}$  cor. for sec. 3, with a brass cap, marked

|  
 $\frac{1}{4}$  S 3  
1913

Dig pits, 18 X 18 X 12 ins. N. and S. of post, 3 ft.

dist., and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft.

high, W. of cor.

50.50 Wagon road, bears N.  $70^{\circ}$  E. and S.  $70^{\circ}$  W.

51.60 Dry wash, 40 lks. wide, 2 ft. deep, course E.

64.50 Dry wash, 50 lks. wide, 3 ft. deep, course E.

80.77 Intersect N. bdy. of township 1.30 chs. N.  $89^{\circ}43'$  E. of the cor. of secs. 34 and 35.

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for closing cor. for secs. 2 and 3, with a brass cap, marked

T 33 N R 37 E  
S 34 | S 35  
S 3 | cc  
S 2  
T 32 N  
1913