

Subdivision of T. 32 N., R. 37 E.

*Surveyed by Alex J. Harris*

Chains West to closing cor. bet. secs. 30 and 31.  
 Desc. over rough mountainous land, covered with scattering sage-brush.  
 Desc. 570 ft.  
 24.00 Enter Rock Hill Cañon, bears N. 25° W.  
 25.50 Creek in bottom of canon, 10 lks. wide, <sup>2 ins. deep</sup> course N. 25° W.  
 27.00 Leave cañon, asc. 500 ft.  
 33.50 Top of ridge, bears N. and S.  
 Desc. 200 ft.  
 38.00 Gulch, 30 lks. wide, 7 ft. deep, course N. 10 W., asc.  
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor., with a brass cap, marked

$\frac{1}{4}$  S 30

S 31


1913

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

Asc. 700 ft.

50.50 Top of high ridge, bears N. 20° E., and S. 20° W., desc.  
 66.00 Head of gulch, 10 lks. wide, course N., asc.  
 70.80 Intersect W. bdy. of township 8.55 chs. N. 0° 04' W. of the cor. of secs. 25 and 36.  
 Set an iron post, 3 ft. long, 2 ins. in diam., 8 ins. in the ground to bed rock, in a mound of stone, for closing cor. of secs. 30 and 31, with a brass cap, marked

T 37 N



1913

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

Land rough mountainous.

Soil clay loam, 3rd. rate.