

## Resurvey of the E. bdy. of T. 37 N., R. 38 E.

Chains

cor., with a brass cap, marked

$$\begin{array}{c} \frac{1}{4} \text{ S } 12 \mid \text{ S } 7 \\ 1913 \end{array}$$

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

N.  $0^{\circ} 10'$  W. on a true line on the N. half mile bet. secs. 7 and 12.

80.47

Intersect old cor. of secs. 1, 6, 7 and 12.

I destroy all trace of the old cor. and at same point

Set an iron post, 3 ft. long, 3 ins. in diam., 24 ins.

in the ground for a new sec. cor., with a brass cap, marked

$$\begin{array}{c} \text{T } 37 \text{ N} \\ \text{R } 38 \text{ E} \mid \text{R } 39 \text{ E} \\ \text{S } 1 \mid \text{S } 6 \\ \text{S } 12 \mid \text{S } 7 \\ 1913 \end{array}$$

Dig pits, 18 X 18 X 12 ins., in each sec.,  $5\frac{1}{2}$  ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land level.

Soil sandy, 3rd. rate.

Undergrowth scattering sage-brush.

Drains SW.

---

N.  $0^{\circ} 3'$  W. on a true line bet. secs. 1 and 6.

Over level land covered with scattering sage-brush.

40.00

Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for  $\frac{1}{4}$  cor. for sec. 1, with a brass cap, marked

$$\begin{array}{c} \frac{1}{4} \text{ S } 1 \mid \\ 1913 \end{array}$$

Dig pits, 18 X 18 X 12 ins. N. and S. of post, 3 ft. dist. and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high W. of cor.

40.57

Intersect the old  $\frac{1}{4}$  sec. cor.

I destroy all trace of the old cor., and at same point

Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in

the ground for  $\frac{1}{4}$  cor. of sec. 6, with a brass cap,

marked.