

Chains.

- and raise a mound of stone 2 ft. base $1\frac{1}{2}$ ft. high N. of cor.
- 45.20 Rocky mountain spur, slopes S.
- 56.90 Small ravine, course southerly.
- 59.30 Deep ravine, course S.E.
- 70.32 Intersect the W. ldy. of the tp. at N. 30.38 chs. from the cor. of secs. 1, 6, 7 and 12. which cor. is an iron post, firmly set in the ground, of the dimensions and marked and witnessed as described by the Surveyor General.
- On steep N.E. slope of mountain spur. Set a basalt rock $15 \times 10 \times 6$ ins., 10 ins. in the ground for closing corner of secs. 6 and 7, marked CC on E. face with 5 grooves on S. and 1 groove on N. face and raise a mound of stone 2 ft. base $1\frac{1}{2}$ ft. high E. of cor.
- Land, rough volcanic mountains. Soil, rocky, unfit for cultivation. 4th. rate. Good growth sagebrush, little grass, scattering junipers and mahogany on W. 35 chs. Southwesterly slope.

On the W. ldy. of sec. 7 at a point midway between the closing corners of secs. 7 and 18, and secs. 6 and 7, set a basalt stone, $17 \times 11 \times 7$ ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor. W. of sec. 7, marked $\frac{1}{4}$ on the E. face and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high E. of cor.

On the W. ldy. of sec. 6, at a point 40.00 chs N. of the closing corner of secs. 6 and 7, set a basalt stone $16 \times 10 \times 5$ ins. 11 ins. in the ground for $\frac{1}{4}$ sec. cor. West of sec. 6, marked $\frac{1}{4}$ on the E. face and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high E. of cor.