


Subdivision of fracl. T. 41 N., R. 36 E.

- Chains and dig pits, 18 X 18 X 12 ins. E. and W. of post, 3ft. dist., and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.
- 74.10 Wagon road, bears N. and S.
- 76.00 Wire fence, bears N. 20° E. and S. 20° W., leave sage-brush enter open grass land, bears N. and S.
- 80.90 Intersect the W. bdy. of the township 5.97 chs. N. 0° 28' W. of the cor. of secs. 12 and 13. previously described. Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for closing cor. of secs. 7 and 18, with a brass cap, marked



and dig pits, 18 X 24 X 12 ins., crosswise of the line, N. and S. 3 ft. dist., and E. 7 ft., and raise a mound of earth, 4 ft. base, 2 ft. high, E. of cor.

Land level.

Soil clay loam and sandy with some adobe and alkali spots, clay sub-soil, 3rd. rate.


Undergrowth scattering sage-brush and grease-wood, 2 ft. high.

Drains W. into Quinn river.

From the closing cor. of secs. 7 and 18, I run S. 0° 28' E. on the W. bdy. of sec. 18.

- 5.97 Cor. of secs. 12 and 13. previously described. Thence S. 0° 6' W. on same line.

- 39.93 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for ¼ cor. for sec. 18, with a brass cap, marked



and dig pits, 18 X 18 X 12 ins. N. and S. of post, 3