

4. Resurvey of the E. Bdy. of T.42 N., R. 60 E.

Chs.

containing great deal of lime. Very rocky. Many stones and huge boulders of limestone. North of creek, to spur at 64.20, soil is decomposed rock; coarse gravel and stones, containing a little loam. Many outcrops of solid volcanic rock. North of spur, soil is rich, black loam, several feet deep. Many outcrops of yellow, shaly rock.  
 Aspen timber along creek. A few mountain mahogany trees on spur at 63.90 chs.  
 Undergrowth of willows, sage, buck and service berry brush. Some grass throughout mile. Abundant growth at N. end of mile.

N.0°38'E. on a resurvey of E. Bdy. of sec. 12.  
 Over heavily rolling land.

18.90 Draw, 160 ft. below section corner, course E.  
 39.31 Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. of sec. 12, with brass cap mkd:

S12 $\frac{1}{4}$  |  
 1914

and raise a mound of stone 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

40.60 Spur, 185 ft. above draw, bears E.  
 49.60 Draw, 45 ft. below spur, course SE.  
 61.20 Spur, 130 ft. above draw, bears SE.  
 66.20 Draw, 50 ft. below spur, course E.  
 77.70 Ridge, 110 ft. above draw, bears E. and W.  
 78.61 Set an iron post 3 ft. long, 3 ins. in dia., 24 ins. in the ground for the cor. of secs. 1 and 12, with brass cap mkd:

T42N  
 R60E  
 S 1  
 ————  
 S 12

1914

and raise a mound of stone 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

Corner is 20 ft. below ridge.  
 Land, heavily rolling.  
 Soil is rich, black loam, on subsoil of clay and gravel.  
 Scattering stones and a few outcrops of solid rock.  
 No timber.  
 Undergrowth of sage, buck, and service berry brush.  
 Abundant growth of grass throughout mile.

N.0°38'E. on a resurvey of E. Bdy. of Sec. 1.  
 Over heavily rolling land.

6.30 Bottom of draw, 40 ft. below sec. cor., course N.60°W.  
 15.20 Spur, 65 ft. above draw, bears W.  
 24.50 Draw, 50 ft. below spur, course SW.  
 37.30 Spur, 55 ft. above draw, bears SW.  
 39.31 Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. of sec. 1, with brass cap mkd:

S1 $\frac{1}{4}$  |  
 1914

and raise a mound of stone 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

43.00 Stream of water, 1 lk. wide, 1 in. deep, 20 ft. below spur, course S.60°W.  
 56.50 Top of spur, 95 ft. above creek, bears W.  
 60.90 Bottom of draw, 20 ft. below spur, course SW.  
 65.40 Ridge, 60 ft. above draw, bears E. and W.  
 78.30 Draw, 70 ft. below ridge, course N.60°W.  
 78.61 The old cor. of Ts. 42 and 43 N., Rs. 60 and 61 E.,