Resurvey 4th St. Par N. R 65 E

Chains

Course of this ½ mile is N.0°4'E.
Continue N. on same line.
40.20 Barbwire fence, bears E. & W. Enter dense timber.
44.30 Dry irrigation ditch, course S.50°W.
Continue through dense timber, over frequent draws and ridges.
80.10 Old cor. for secs. 25 & 36 bears E. 10 lks.
A basalt rock, 12x5x5 ins. above ground, marked and witnessed as described by the surveyor general.
Course of last ½ mile is N.0°4'E.
Rolling foot hills.
Soil, rocky. 2nd and 3rd. rate.
Dense timber, 56.15 chs.; scrub cedar and pinion pine.

May 4, 1913.

Resurvey 4th St. Par N. R 65 E

May 5, 1913: At 9h 00m A.M., l.m.t., I set off 39° 39' on the lat. arc; 16° 13½' N. on the decl. arc; and determine a true meridian with the solar, at the temp. standard cor. of T. 21N., Rs 64 & 65E., heretofore described and set by myself on April 23, 1913. {This temporary cor. is 4.80 chs. west of the old cor. of T 21N, Rs 65 and 66E., previously referred to}
Thence I run
West, on a retracement.
40.00 Set a temp. ¼ sec. cor.
82.10 Intersect E. bdy. of T. 21N, R 64E., 8.32 chs. N. of ¼ sec. cor. for sec. 36, or 48.32 chs. N. of the cor. for T. 21N., R. 64E., heretofore described.
At point of intersection, I set a limestone, 18x12x5 ins., 12 ins. in the ground, for closing township cor., marked with 6 grooves on S., E. & N. faces, and C.C. on E. face; and raise a mound of stone; 2 ft. base, 1½ ft. high, E. of cor.
The distance from this point to the old cor. marked for T. 21N., Rs. 65 & 66 E. is 562.10 chs.