

Subdivision of T. 15 N., R. 26 E.

Chains

79.94

The cor. of secs. 5, 6, 7 and 8.

Land, gently rolling valley
Soil, sandy loam, stony and
rocky; mostly 3^d rate
Undergrowth, sage and desert brush,
greasewood and some bunch grass
no timber.

Aug. 7, 1913

Aug 6, 1913

Went on a true line bet. secs.
6 and 7.

25.00

Now rolling land, ascending
Top of spur, bears N. and S. desc.

30.00

Gulch, course N. and ascend.

38.30

Crest of ridge, bears N. and S. and
descend

40.00

No iron posts available

Set a trap rock 14 x 6 x 20 ins., 10
ins. in the ground, for $\frac{1}{4}$ sec. cor.
marked $\frac{1}{4}$ 56 on N. face and
5.7. on S. face; build a mound
of stone around the cor.; and
raise a mound of stone 2 ft.
base, 1 1/2 ft. high, N. of cor.

77.33

thence over rolling land, descend
Intersect W. bdy. of Twp. 2. 57 Chs.
N. 10° 25' E of the old cor. of
secs. 1, 6, 7 and 12, hereafter
referring to secs. 1 and 12. of
T. 15 N. R. 25 E. only. At the
point of intersection I build
a cor. as follows:

Set an iron post 3 ft. long,
2 ins. diam., 24 ins. in the