Resurvey of the west bdy. of T. 28 N. R. 39 E.

## Chains.

As most of the old corners are nearly obliterated and some of them are missing I resurvey the lines as follows; Oct. 12, 1914.

Beginning at the corner of Tps. 27 and 28 N. Rs. 38 and 39 E. previously described which I restablish as follows:

Set an iron post 3 ft. long, 3 ins. in dia. 24 ins. in the ground by the side of the old corner., for the re-established corner of Tps. 27 and 28 N. Rs. 38 and 39 E. with brass cap marked

T28N	
R38E	R39E
S36	S31
S1	S6
. R38E	R39E
T 27 N	

and raise mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high south of cor.

North 0° 15' W. on true line bet. secs. 31 and 36.

Over rolling land, through sage brush and shad scale, gradually desc.

- 2.73 Wash, 15 lks. wide, 41 ft. deep, course N. 70° W.
- 10.13 Base of hills, bears NE. and SW., gradually desc. over desert land.
- 17.03 Wash, 1 ch. wide, 2 ft. deep, course N. 80° W.
- 18.23 Wash, 10 lks. wide, 5 ft. deep, course N. 80° W.
- 23.13 Wash, 1.50 chs. wide, 30 ft. deep, course S. 85° W.
- 28.20 Wash, 75 lks. wide, 4 ft. deep, course S. 75° W.
- 40.80 The described. I re-establish same with an iron post 3 ft. long, 1 in. in dia. set 26 ins. in the ground by the side of the old cor. for reestablished described. Sec. cor. of sec. 36, with brass cap marked

\$36\frac{1}{4}

and raise mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high west of cor.

N. 0° 21' W. on true line.