


## Subdivision of T. 28 N. R. 39 E.

## Chains.

59.80 Base of mountains, 510 ft. below spur, bears N.  $10^{\circ}$  E. and S.  $15^{\circ}$  W., gradually desc. over bench land.

75.09 Intersect west bdy. of Tp, 123 lks, S.  $0^{\circ} 21'$  E. of the cor. of secs. 25 and 36. Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in the ground for the closing cor. of secs. 30 and 31, with brass cap marked



and raise mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high east of cor.

Soil, light clay loam, limestone ledges and slide rock to 59.80 chs., thence sandy loam.

Sage brush and bunch grass, fairly good grazing.

No timber.

Mountainous land 59.80 chs. level bench land 15.29 chs.

Oct. 22, 1914.

*H. W. Rippey*  
U.S. Surveyor


Oct. 19, 1914. (Mer. obsn. see line bet. secs. 31 and 32).

N.  $0^{\circ} 03'$  W. bet. secs. 29 and 30.

Over mountainous land through sage brush and scattering junipers, desc.

11.82 Canyon, 160 ft. below cor. course west, asc.

40.00 Set an iron post 3 ft. long, 1 in. in dia. 12 ins. in the ground and in mound of stone for  $\frac{1}{4}$  sec. cor., with brass cap marked



and raise mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high west of cor.

42.45 Ridge, 855 ft. high, bears E. and W., gradually desc.

47.35 Head of canyon, course west, continue desc.

63.50 Ridge, 175 ft. below the last ridge, bears N.  $70^{\circ}$  W. and S.  $70^{\circ}$  E. continue desc.

80.00 Set an iron post 3 ft. long, 2 in. in dia. 24 ins. in the