

Resurvey of Mt. Diablo Base line
through R55E

chains

and raise a mound of stone 2 ft. base
1 1/2 ft. high N. of cor.

I destroy all traces of the old stand
and corner of secs. 31 and 32, and its
accessories.

Land somewhat rolling.

Soil; desert loam, containing much
gravel and rocks. 2nd or 3rd.

Good growth sagebrush, little grass,
no timber, General S. E. slope.

W.; south of sec. 31

Over rolling land.

3.01 Intersect the closing corner of secs.
5 and 6, T1S, R55E; a volcanic stone
firmly set in a mound of stone,
of the dimensions and marked and wit-
nessed as described by the Surveyor General.

8.50 Wash, course S. E.

21.00 Rocky ridge, bears N. and S.

24.60 Wash, course N. E.

40.00 Set an iron post 3 ft. long, 1 in.
diam. 2 1/4 ins. in the ground for standard
1/4 sec. cor. with brass cap mkd.

S 31 1/4
SC

1913

and raise a mound of stone 2 ft.
base, 1 1/2 ft. high N. of cor.

I destroy all traces of the old standard
1/4 sec. cor. and its accessories.

84.00 Intersect the Standard corner of
T1N, R5. 54 and 55 E.

I destroy all traces of this standard
corner and its accessories and re-
establish it at the same point as
follows:

Set an iron post 3 ft. long, 3 ins. diam.
2 1/4 ins. in the ground for standard
cor. of T1N, R5. 54 and 55 E, with