Subdivision of T5N R69E

Chains

with brass cap mkd.

S6 1/4 | S5 ✓
1913

and raise a mound of stone 2 ft. base 1½ ft. high W. of cor.

43.20 Mountain spur, slopes S.W.

61.10 Small ravine, course S.W.

72.00 Enter thick timber

77.31 Intersect the 1st. Standard Parallel North at E. 16.80 chs. from the Standard cor. of Th. 6N, Rs. 68 and 69E., which corner is an iron post, 3 ins. diam., firmly set in the ground, marked and witnessed as described by the Surveyor General

Set an iron post 3 ft. long, 2 ins. diam. 24 ins. in the ground for closing corner of secs. 5 and 6, with brass cap mkd.

S36 | S31
CC ✓
S6 | S5
T5N R69E
1913

and raise a mound of stone 2 ft. base 1½ ft. high S. of cor.

A pine tree 6 ins. diam. bears S24°35'W, 38 lks. dist. marked T5N R69E S6 BT

A pine tree 9 ins. diam. bears S.8°30'E, 41 lks. dist. marked T5N R69E S5 BT.

Land, S. 3.50 chs. and N. 62.81 chs. is rolling, rocky, volcanic mountains; with thin, dry, rocky, soil. 4th. rate, unfit for cultivation. From 3.50 ch. pt. to 14.50 ch. pt. it is level land in Camp Valley wash, good, deep, sandy loam soil, derived from washing down from surrounding volcanic mountains. 1st. rate.

On N. 5.31 chs. is thick juniper and scrub pine timber, on rest of mountain land there are a few scattering