

Chains

73.10 Spur, slopes westerly.

78.04 The cor. of secs. 2 and 11.

80.60 The closing corner of secs. 3 and 10.

Land; steep rocky, volcanic mountain slopes; sloping to the NW.

Soil; poor, rocky and gravelly, shallow and quite dry, 4th rate. Fair growth of sagebrush, not much grass.

No timber.

August 28, 1914.

October 18, 1913: From the cor. to secs. 2 and 11, previously set, I run

N.0°02'W. on a true line between secs. 2 and 3. Descending.

2.80 The C.C. to secs. 3 and 10.


8.40 Draw, course W. Ascend along W. side of ridge.

40.00 Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground, for 1/4 cor. of sec. 2 only, with brass cap mkd:



dig pits 18x18x12 ins. N. and S. of post 3 ft. dist., and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high, E. of cor.

42.80 Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for 1/4 cor. of sec. 3 only, with brass cap mkd:



dig pits 18x18x12 ins. N. and S. of post 3 ft. dist., and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

This cor. will be regarded as a witness cor. for sec. 3, situated 51 lks. S.0°02'E. of true point for 1/4 sec. cor. for sec. 3.

43.31 True point for 1/4 sec. cor. for sec. 3.

84.23 Intersect N. Bdy. of Tp. at a point 1.38 chs. S.89°34'W. of the cor. to secs. 34 and 35; previously described.

Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for C.C. of secs. 2 and 3, with brass cap mkd: