

Subdivision of T 33 N, R 46 E.

Chains

ground for $\frac{1}{4}$ sec. cor. with brass cap mkd.

S 12 $\frac{1}{4}$

S 13
1914

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

Desc. 30 ft. to

44.00 Bottom of slope, thence over rolling Mesa land.

78.20 Intersect the E. bdy. of the tp. at N $2^{\circ}14'W$, 2.30 chs. and 18 from the cor. of secs. 7, 12, 13, previously described by Transitman Collins. This cor. now refers to secs. 7 and 18 only. Set an iron post, 3 ft. long, 3 ins. diam. 24 ins. in the ground for cor. of secs. 12 and 13, with brass cap mkd.

T 33 N
R 46 E R 47 E
S 12

S 13
1914

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

Land; W. 19.80 and E. 34.20 chs. is high, rolling mesa.

From 19.80 to 44.00 ch. point is steep, S.E. slope, covered with slide and rimrock.

Soil; on W. 19.80 and E. 34.20 chs. is fair quality soil but shallow, underlaid at a little depth with a volcanic bed rock. 3rd. rate. Good growth sagebrush and considerable grass on this part of the mile. From 19.80 to 44.00 ch. point there is but little soil or vegetation. Practically worthless.

S $0^{\circ}4'W$, bet. secs. 13 and 14.

Over high, rolling, mountain mesa.

17.40 Edge of rim rock, bears N.E. and S.W. Desc. over steep S.E. slope, over slide and rim rock. Desc. 400 ft. to

33.65 Bottom of steep slope, thence over rolling mesa

40.00 Set an iron post, 3 ft. long, 1 in. diam. 24 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

S 14 $\frac{1}{4}$ | S 13

1914

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

61.20 Begin desc. of S. slope. Desc. 200 ft. to

76.00 Draw, course S.W.