

10.

Resurvey of Subdivision in T.35 N., R. 46 E.

Chains

T35N
R46E
S9

dig a pit 36x36x12 ins., in the sec. 8 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, NE. of cor.

Land gently rolling.

Soil, sandy 2nd rate.

Undergrowth, sagebrush and bunchgrass.

No timber.

The above mile was examined on Aug. 20, 1914, by Winfred A. Pray, U.S. Surveyor, and found correct.

Resurvey Aug. 21, 1914, by U.S. Surveyor Winfred A. Pray  
From the S. W. corner of section 9, previously described in the notes of Transitman Collins, I resurvey N. on a random line

161.40 Fall 61 lks W. of the closing cor. to secs. 4 and 5, reestablished by me Oct. 25.

Thence I run

S.0°13'W. bet. secs. 4 and 5.

Over rolling land.

18.40 Wash, course S.75°E.

29.80 Road, bears easterly and westerly.

38.40 Wash, course easterly.

40.80 (Proportional distance) Set an iron post 3 ft. long, 1 in. in diam., 24 ins. in the ground for  $\frac{1}{2}$  sec. cor. with brass cap mkd:

S5 1/4	S4
1914	

dig pits 18x18x12 ins., N. and S. of post 3 ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

45.70 Wash, course easterly.

73.80 Wash, course easterly.

81.00 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground for cor. of secs. 4 and 9, with brass cap mkd:

T 35 N	
R 46E	
S4	
S 9	
1914	

dig pits, 24x24x12 ins. in each sec., 6 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, E. of cor.

Land; rolling land with a general slope to the E.

Soil, fair quality, medium texture loam from 1 to 2 ft. in depth; derived from the disintegration of volcanic rock. Contains considerable gravel. Underlaid with a firm, rocky subsoil, 3rd rate.

Fair growth sagebrush, not much grass, no timber.

Retraced August 21, 1914; by Winfred A. Pray, U.S. Surveyor  
From the closing corner of secs. 4 and 5, previously described in the notes of Transitman Collins.

I retrace N.89°42'W. on the 7th Standard Parallel North, on the N. Bdy. of Sec. 5.

6.27 The Standard  $\frac{1}{4}$  sec. cor. for sec. 32.

40.00 Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. for sec. 5, with brass cap mkd:

S 5 1/4
1914

and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of cor.