


Chains



dig pits 24x18x12 ins., crosswise on each line, N. and S. 3 ft. and W. of post 7 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, W. of cor. Land, W. 41.00 chs. is NE. slope of rocky, volcanic mountain. E. 41.44 chs. is rolling land, with a general slope to the SE. Soil; W. 41.00 chs. is poor, very rocky, dry and shallow, 4th rate. E. 41.44 chs. is fair quality, coarse texture loam, from a few inches to a foot in depth. Underlaid with a firm, clay subsoil. Quite dry, 3rd rate. Fair growth sagebrush, not much grass, no timber.

Retraced Aug. 27, 1914, by U.S. Surveyor, Winfred A. Pray.

40.00

From the closing corner of secs. 5 and 8, I run N.89°54'W. bet. secs. 5 and 8. Set an iron post 3 ft. long, 1 in. in diam., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor., for sec. 5, with brass cap mkd:




and raise a mound of stone 2 ft. base, 1½ ft. high, N. of cor.

Surveyed Aug. 27, 1914, by U.S. Surveyor Winfred A. Pray.

10.80  
15.90  
37.50  
40.00  
60.70  
82.54

From the cor. of secs. 5, 6, 7 and 8, I run N.0°1'W. bet. secs. 5 and 6. Descending NE. slope of volcanic mountain. Ravine, course NE. Ascend SE. slope. Mountain spur, slopes NE. Desc. NE. slope. Foot of mountain, bears NW. and SE. Descend gradually over rolling land. Set temp.  $\frac{1}{4}$  sec. cor. Road, bears easterly and westerly. Intersect the 7th Standard Parallel North, at N.89°42'W. 36.26 chs. from the Standard cor. of secs. 31 and 32. Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground for closing corner of secs. 5 and 6, with brass cap mkd:



and raise a mound of stone 2 ft. base, 1½ ft. high, S. of cor. Land; S. 37.50 chs. is rocky, N.E. slope of mountain. N. 45.04 chs. is rolling land, sloping to the NE. Soil; S. 37.50 chs. is poor, rocky, land on slope of mountain 4th rate. N. 45.04 chs. is rather poor, sandy and gravelly loam, from a few inches to a foot in depth, 3rd rate. Fair growth sagebrush, not much grass, no timber.