

## 24. Survey of Subdivisions in T.35 N., R. 46 E.

Chains

Retraced Aug. 27, 1914; by U.S. Surveyor, Winfred A. Pray.  
From the closing corner of secs. 5 and 6, on the 7th  
Standard Parallel North, I run

40.64 S.0°1'E. bet. secs. 5 and 6, retracing.  
(Proportional distance) Set an iron post 3 ft. long,  
1 in. in diam., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor.  
with brass cap mkd:

$$\begin{array}{c} S6\frac{1}{4} \quad | \quad S5 \\ \hline 1914 \end{array}$$

and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

From the cor. of secs. 5, 6, 7 and 8, I run  
W. bet. secs. 6 and 7.

4.00 Ascending NE. slope of rocky mountain.  
Mountain spur, slopes NE., 60 ft. above sec. cor.  
11.30 Ravine, course NE. Asc. steep NE. slope.  
23.60 Top of mountain, bears NW. and S., 430 ft. above ravine.  
Desc. steep SW. slope.  
40.00 On steep SW. slope, 370 ft. below mountain top.  
Set an iron post 3 ft. long, 1 in. in diam., 24 ins. in  
the ground for  $\frac{1}{4}$  sec. cor., with brass cap mkd:

$$\begin{array}{c} S6\frac{1}{4} \\ \hline S7 \\ \hline 1914 \end{array}$$

and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor.

42.00 Mountain spur, slopes S.  
52.15 Wash, course S. 145 ft. below mountain spur.  
63.20 Rocky mountain spur, slopes S. 60 ft. above wash.  
68.00 Wash, course S. 40 ft. below mountain spur.  
72.80 Mountain spur, slopes SW., 30 ft. above wash.  
75.14 Intersect the W. bdy. of the Tp. at S.0°5'E., 1.67 chs.  
from the cor. of secs. 1 and 12.

Set an iron post 3 ft. long, 2 ins. in diam., 24 ins.  
in the ground for closing corner of secs. 6 and 7, with  
brass cap mkd:

$$\begin{array}{c} T\ 35\ N \\ R45E \quad | \quad R46E \\ \hline S1 \quad | \quad S6 \\ \hline CO \quad | \\ \hline S12 \quad | \quad S7 \\ \hline 1914 \end{array}$$

and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high,  
E. of cor.

Land; high, rough, volcanic mountains. E. 23.60 chs.  
slopes to the NE. W. 51.84 chs. slopes to the SW.  
Soil, poor and rocky. Many ledges and rocks in place,  
4th rate.

Some sagebrush among the rocks. Not much grass, no  
timber.

Retraced Aug. 27, 1914; by U.S. Surveyor Winfred A. Pray.  
From the closing corner of secs. 6 and 7, on the W.  
bdy. of the township, I run

38.10 S.0°5'E. bet. secs. 7 and 12, retracing.  
40.06 The  $\frac{1}{4}$  sec. cor. for sec. 12.  
Set an iron post 3 ft. long, 1 in. in diam., 24 ins. in  
the ground for  $\frac{1}{4}$  sec. cor. for sec. 7, with brass cap  
mkd:

$$\begin{array}{c} | \quad S\ 7\frac{1}{4} \\ \hline 1914 \end{array}$$

and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high,  
E. of cor.