

## Re-survey of S. bdy. of T 34 N, R 47 E.

Chains	dig pits 18-18-12 ins. E. and W. of post, 3 ft. dist. and
	raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high N. of cor.
78.70	Dry slough, 30 lks. wide, course S.E.
80.60	At this point; the proper proportional distance bet. the
	cor. of secs. 2, 3, 34 and 35; and the cor. of Tps. 33 and
	34 N., Rgs. 47 and 48 E.
	Set a basalt stone, 16-14-10 ins.; 12 ins. in the ground
	for cor. of secs. 1, 2, 35 and 36; mkd. with 1 notch on the
	E. and 5 notches on the W. edge; dig pits 18-18-12 ins.
	in each sec. $5\frac{1}{2}$ ft. dist. and raise a mound of earth 4 ft.
	base, 2 ft. high W. of cor.
	Land; W. 27 chs. is gradual S.E. slope. E. 51.60 chs.
	is level land in the Humboldt River bottom.
	Soil; W. 27 chs. is poor and shallow, very rocky and dry.
	3rd. rate. E. 51.60 chs. is deep, rich, fertile loam in
	the river bottom. 1st. rate, with irrigation would produce
	excellent crops. Short sage brush on W. 27 chs. little
	grass. On E. 51.60 chs. is big sage brush, grease wood, and
	rye grass.
	<hr/>
	N $89^{\circ}20'$ E, bet. secs. 1 and 36.
	Over level bottom land.
8.70	Dry slough, 25 lks. wide, course S.E.
37.00	Dry slough. 30 lks. wide, course S.E.
40.30	At this point; the proper proportional distance bet. the
	cor. of secs. 2, 3, 34 and 35; and the cor. of Tps. 33 and
	34 N, Rgs. 47 and 48 E,
	Set an iron post, 3 ft. long, 1 in. diam. 24 ins. in the
	ground for $\frac{1}{4}$ sec. cor. with bras cap mkd.
	S $36\frac{1}{4}$
	-----
	S 1
	1914
	dig pits 18-18-12 ins. E. and W. of post, 3 ft. dist.
	and raise a mound of earth, $3\frac{1}{2}$ ft, base, $1\frac{1}{2}$ ft. high N. of cor.
80.60	The cor. of Tps. 33 and 34 N, Rgs. 47 and 48 E.
	I destroy all traces of this cor. and its accessories and