Chains

T30N R42E | R43E SI 1914

Dig pits, 24x24x12ins. in each sec. 6 ft. dist. and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high W. of corner.

Land; valley, sloping gently southward.
Soil; sandy and dry clay loam fine texture, 10 ins.
deep; hard clay subsoil.

. Under growth: sage and desert brush, some greasewood. No timber.

3.09

From the cor. of secs. 1 and 12, I run N. 0° 15'W. The old cor. of secs. 1, 6, 7 and 12, heretofore described.

I reestablish the corner as follows: Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground for the cor. of secs. 6 and 7, with a brass cap mkd.,

> T30N R42E! R43E **S6**

Dig pits, 24x24x12ins., in each sec. 6 ft. dist. and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high E. of

I now change the bearing and run
N.0° 14'W., the course and distance of this mile by previous retracement.

Set am iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., with brass cap mkd.,

S 1 1 1914

Dig pits 18x18x12ins, N. and S., of post, 3 ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high W. of corner.

The pits and mound of earth of the old 4 sec. cor., I reestablish the cor. of \$\frac{1}{4}\$ sec. at the same point . as follows:

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for & sec. cor., with brass cap mkd.,

1914

Dig pits, 18x18x12ins. N. and S. of post, 3 ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high E. of corner.

Wagon road, bears S. 85°E. and N. 85°W. Wagon road, bears N. 50°W. and S. 50°E.

Wash, 50 lks. wide, course S. 45 W.

The old closing cor. of Tps. 30 N., Rs. 42 and 43 E., heretofore described. I destroy the old cor. and re-establish the same at the center of the mound of earth as follows:

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in

40.00

43.11

53,35 60.53

82.85 84.98