


Chains

61.30
85.47

Dig pits, 18x18x12ins., N. and S. of post, 3 ft. dist., and raise a mound of earth 3½ ft. base, 1½ ft. high W. of corner.
Wagon road, bears N. 50°E. and S. 50°W.
Intersect the 6th Standard Parallel North, at 28.73 chs. N. 89° 56'W. of the Standard corner of secs. 35 and 36, T. 31 N., R. 42 E.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for C.C. of secs. 1 and 2, with brass cap mkd.,



Dig pits, 24x18x12ins., crosswise on each line, E. and W. 3 ft. dist. and set stone 7 ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high S. of corner.
Land; valley, drains S.W.
Soil; dry sandy light clay loam, fine texture, 14 ins. deep, hard clay subsoil.
Undergrowth, sage and desert brush.
No timber.

June 26, 1914.

Surveyed by H.W.Reppert:-
June 25, 1914:- At 8h.45m., a.m., l.m.t., I set off 40°26' N. on the lat. arc; 23° 25'N. on the decl. arc and determine a meridian with the solar at the cor. of secs. 25, 26, 35 and 36.
Thence I run
West on a true line bet. secs. 26 and 35.
Over rolling hills volcanic formation; ascend.
Top of ridge, 60 ft. above sec. cor., bears N. 80°E. and S. 45° W.; ascend along N. slope of ridge, 80 ft.
Descend along N. slope 180 ft. to the ¼ sec. cor.
Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock and in a mound of stone, for ¼ sec. cor., with brass cap mkd.,

4.00
18.00
40.00



68.95
77.25
80.00

and raise a mound of stone, 2 ft. base, 1½ ft. high N. of corner.
Wagon road, bears N. and S., in wash, 15 lks. wide, course N.
Leave foot hills, bears N. E. and S. W.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.,



and raise amount of stone, 2 ft. base, 1½ ft. high W. of corner.
Land, rolling foothills, volcanic formation.
Soil; rocky loam, covered with lava boulders, outcropping barren ledges.
Undergrowth; sage and desert brush.
No timber.