

22.

Subdivisions of T. 30 N., R. 42 E.

Chains

of corner.
 69.00 Road, bears E. and W.
 79.25 Wash, course S. 45°W.
 85.64 Intersect the 6th Standard Parallel North 28.24 chs.
 N. 89° 55'W. of the Standard Corner of secs. 34 and 35,
 heretofore described.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
 the ground for closing corner of secs. 2, and 3, and
 3, with brass cap mkd.,

T31NR42E
 S34 | S35

 C | C
 S3 | S2
 1914

Dig pits, 24x18x12ins., crosswise on each line, E. and
 W., 3 ft. dist. and S. of stone 7 ft. dist. and raise a
 mound of earth 4 ft. base, 2 ft. high, S. of corner.
 Land; valley with gentle slope Southward.
 Soil; sandy and gravelly dry loam, fine texture, 14 ins.
 deep, hard clay subsoil.
 Undergrowth, sage and desert brush.
 No timber.

June 26, 1914.

Surveyed by A.T.Harris:-

June 26, 1914: At 8h.10m., a.m., l.m.t., I set off 40°
 27'N. on the lat. arc; 23° 24'N. on the decl. arc; and
 determine a meridian with the solar at the cor. of secs.
 22, 23, 26 and 27.

Thence I run

West on a true line bet. secs. 22 and 27.

Over level land, drains S. W.

6.00 Wash, 50 lks. wide, course S. 75°W.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.,

S22
 $\frac{1}{4}$

 S27
 1914

80.00 Dig pits, 18x18x12ins. E. and W. of post, 3 ft. dist.,
 and raise mound of earth 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high N.
 of corner.
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
 the ground for cor. of secs. 21, 22, 27 and 28, with
 brass cap mkd.,

T30NR42E
 S21 | S22

 S28 | S27
 1914

Dig pits, 18x18x12ins., in each sec. 5 $\frac{1}{2}$ ft. dist., and
 raise a mound of earth 4 ft. base, 2 ft. high W. of cor.
 Land; flat alkali desert.
 Soil; moist sandy clay loam, alkali.
 Undergrowth, greasewood.
 No timber.

N: 0° 16'W. bet. secs. 21 and 22.