

Subdivisions of T. 30 N., R. 42 E.

31.

Chains
69.80

Intersect W. bdy. of Tp. 6.35 chs. S.0° 21'W. of the cor. of secs. 1, 6, 7 and 12, heretofore described. I obliterate the markings on this corner referring to secs. 6 and 7, of T. 30 N., R. 42 E. and at point of intersection set the corner as follows:-
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for closing corner of secs. 6 and 7, with brass cap mkd.,

T30N
R41E | R42E
S1 |
S12 | CS6
 | CS7
1914

Dig pits, 24x18x12ins. crosswise on each line, N. and S., 3 ft. dist. and E. of post 7 ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high E. of corner. Land; valley, drains S.
Soil, loose light clay loam, 14 ins. deep, compact clay subsoil.
Undergrowth, sage and desert brush.
No timber.

40.00

N.0° 18'W. bet. secs. 5 and 6.
Over valley land, drains S.
Set an iron post, 3 ft. long, 26 ins. in the ground, 1 in. in diam., for $\frac{1}{4}$ sec. cor., with brass cap mkd.,

S6 $\frac{1}{4}$ | S5
1914

86.26

Dig pits, 18x18x12ins., N. and S. of post, 3 ft. dist., and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W. of corner.
Intersect the 6th. Standard Parallel North 27.56 chs. N. 89° 53'W. of the Standard Corner of secs. 31 and 32.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for closing cor. of secs. 5 and 6, with brass cap mkd.,

T31NR42E
S31 | S32
C | C
S6 | S5
1914

Dig pits, 24x18x12ins. crosswise on each line, E. and W., 3 ft. dist., and S. of post 7 ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high S. of corner. Land; valley drains S.
Soil; loose light clay loam, fine texture, 12ins. deep, gravelly clay subsoil.
Undergrowth, sage and desert brush.
No timber.

June 27, 1914.