

24.

Subdivision of T.29 N., R. 43 E.

Chains

and raise a mound of stone 2 ft. base, 1½ ft. high,  
S. of cor.

49.00 Top of ridge, bears S. 10° E. and N.10°W., desc.

76.80 Dry wash, 30 lks. wide, course S. 30° E., asc.

79.58 Intersect the W. bdy. of the township, 67 lks. S.0°13'  
E. of the cor. of secs. 1 and 12 of T. 29 N., R. 42 E.

At the point of intersection, I set a granite stone,  
6x8x18 ins., 10 ins. in the ground for closing cor.  
of secs. 6 and 7, marked with 5 grooves on the S. face  
and 1 groove on the N. face, and 6 grooves and CC on  
the E. face, and raise a mound of stone 2 ft. base,  
1½ ft. high, E. of cor. No iron post available.

Land rolling.

Soil, stony and rocky, clay loam.

Undergrowth, sage and desert brush, greasewood.

No timber.

Land unsuitable for agriculture.

July 1, 1914.

Surveyed by H. W. Reppert:-

Mar. 25, 1915: At 9 h 0 m a.m., I set off 40°24'N. on  
the lat. arc; 1°36'N. on the decl. arc; and determine  
a meridian with the solar at the closing cor. of  
secs. 6 and 7 on the west boundary.

Thence I run

East on a true line on the south boundary of sec. 6.

37.54 The record distance for the length of the S. bdy. of  
the N.W. ¼ of sec. 6, at which point I build a cor.  
as follows:

Set an iron post 3 ft. long, 1 in. in dia., 4 ins. in the  
ground to solid rock and in a mound of stone for the  
¼ cor. of sec. 6, with a brass cap mkd:

S 6  
¼

1915

and raise a mound of stone 2 ft. base, 1½ ft. high,  
N. of cor. Mar. 25, 1915.

X