

Resurvey of W. bdy. of T. 32 N., R. 43 E.

Chains.

Resurveyed by H. W. Reppert:-

From the S. W. cor. of T. 32 N. R. 43 E., which is an iron post, heretofore described

Thence I run

North 38' E., on a true line along W. bdy. of sec. 31.

From head of draw course W., ascend steep S. W. slope

- 6.51 Intersect the S. E. cor. T. 32 N. R. 42 E., which is a limestone, heretofore described. I destroy the markings on the E. side of stone, also fill up the pits on the E. side; dig ^{pits} 30 x 24 x 12 ins., on each line, N. and S., 4 ft. dist., and W. of stone, 8 ft. dist.; and raise a mound of earth, 5 ft. base, 2½ ft. high,

W. of cor.

Thence N. 0° 6' W.,

- 24.80 Top of ridge, bears N. 20° W. and S. 30° E., 225 ft. above the twp. cor.; descend.

- 39.00 Draw 77 ft. below ridge, course S. E.; ascend.

- 40.00 Saddle of same ridge, 35 ft. above draw, N.E. and S. W. Set an iron post, 3 ft. long, 1 in. in dia., 24 ins. in the ground, for ¼ cor. of sec. 31, with a brass cap marked

| ¼ S 31

1914

and raise a mound of stone, 2 ft. base, 1½ ft. high E. of cor.

Descend N. W. slope, slightly.

- 46.15 Intersect the ¼ cor. of secs. 31 and 36, which is an iron post, heretofore described. I obliterate the markings on the E. side of post, making it a ¼ cor. for sec. 36 only.

- 80.00 Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground, for cor. of secs. 30 and 31, with a brass cap marked

E 30 E

R 43 E

E 30

1914

1914