


Resurvey of Portion of Subdivisions of T. 31 N., R. 44 E.

Chains

Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for the  $\frac{1}{4}$  cor. of secs. 5 and 6, with brass cap mkd.:




dig pits, 18 x 18 x 12 ins., on each line, N. and S. of cor., 3 ft. dist.; and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

I now change bearing and run N.  $0^{\circ} 47'$  W., the course and distance of this  $\frac{1}{2}$  mile having been determined by previous retracement.

80.59 Intersect the Hatch and Eaton south Boundary of T. 32 N., R. 44 E., at a point 13.62 chs. S.  $89^{\circ} 36'$  E. of the cor. for. secs. 31 and 32 on this boundary heretofore described. At the point of intersection I build a cor. as follows:

Set an iron post 3 ft. long, 3 ins. diam., 24 ins. in the ground for the cor. of secs. 5 and 6, with brass cap mkd.:



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of cor.

87.95 The old cor. of secs. 5, 6, 31 and 32 of the Maxson survey. I obliterate the markings on the cor., and leave it in the original location as evidence of the original meridional sec. line.

Land, slightly rolling valley.  
Soil, rocky and gravelly clay loam.  
Undergrowth, sage and desert brush.  
No timber.

From the cor. of secs. 5 and 6, set at the intersection of the line bet. secs. 5 and 6, with the Hatch and Eaton south boundary of T. 32 N., R. 44 E. I run