

Survey of Subdivisions of T. 32 N., R. 44 E.

Chains

Surveyed by A.T.Harris:-

July 7, 1914: At 8h. 05m., a.m., l.m.t., I set off $40^{\circ} 35'$ N. on the lat. arc; $22^{\circ} 39'$ N. on the decl. arc; and determine a meridian with the solar at the cor. of secs. 35 and 36, on the south boundary of the township.

Thence I run

North on sectional Guide Meridiane bet. secs. 35 and 36.

33.57 Set temp. $\frac{1}{4}$ sec. cor.

73.57 Set a temp. point for the cor. of secs. 25, 26, 35 and 36, From the temp. point for these secs. I run east on a blank line bet. secs. 25 and 36 and at 83.48 chs., intersect the east boundary of the township 20 lks. S. of the cor. of secs. 25 and 36, thence from the cor. of secs. 25 and 36, I run

West on a sectional Correction line bet. secs. 25 and 36 Over valley land, gradually ascending.

18.98 Telephone line bears N.E. and S.W.

43.48 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for the $\frac{1}{4}$ cor. of secs. 25 and 36, with brass cap mkd.:

S25
 $\frac{1}{4}$

S36

1914

dig pits, 18 x 18 x 12 ins. on each line, E. and W. of cor., 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

71.00 Cross wagon road, bears S. 60° E. and N. 60° W.

78.50 Ascend north slope of hill.

83.48 Intersect N. and S. line, 20 lks. N. of the temp. point previously set for the cor. of secs. 25, 26, 35 and 36. At the point of intersection I build a cor. as follows: Set an iron post 3 ft. long, 2 ins. diam., 20 ins. in the ground to solid rock and in a mound of stone, for the cor. of secs. 25, 26, 35 and 36, with brass cap mkd.: