•		Subdivision of T. 29 N., R. 46 E.
	Chains	S. bet. secs. 23 and 24 on a sectional guide meridian
	0.70 21.80 30.20 35.62	Over somewhat rolling land, sloping to the S.E. Wash, course E. Wash, course E. Wash, course E. Telephone line, bears N. E. and S. W.
	39 <b>.30</b>	Wash, course S. E. In wash, course S. E. Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground for $\frac{1}{2}$ sec. cor with brass cap mkd
	2.33	S 23 ½ S 24
	45.80 55.00 59.00 79.00 80.00	and raise a mound of stone, 2 ft. base, $l\frac{1}{2}$ ft. high W. of corner.  Wash, course S. E.  Wash, course E.  Road, bears S. E. and N. W.  Wash, course S. E.  Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for cor. of secs. 23, 24, 25 and 26, with
		brass cap mkd.,
		R 47 E S 23   S 24 S 26   S 25 1914
		and raise a mound of stone, 2 ft. base, $l\frac{1}{2}$ ft. high W. of corner.  Land; rolling land, with slope to the E.  Soil; rather poor quality, coarse texture loam. From 6 ins. to a foot in depth, underlaid with a firm rocky
•		subsoil. Fair growth short sagebrush and shadscale, very little grass, no timber.
		S. 89° 43'E. on a true line bet. secs. 24 and 25
	3.85 7.25	Over land sloping to the E. Wash, course S. E. Road, bears N. E. and S. W.
	32.70 35,25	Road, bears S. E. and N. W. Wash, course S. E.
	35.10	Road bears N. E. and S. W.
*	40,00	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.,
9		S 24 1 S 25 1914
		Dig pits, $18x18x12ins.$ , E. and W. of post, 3 ft. dist, and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high N.
	54.85	of corner. Wash, course S. E.
	65.35 83.89	Road, bears N. E. and S. W. Intersect the E. bdy. of the tp. at N. 1° 53 E. 28 lks.
		from the cor. of secs. 19 and 30. Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in
	41111	the ground for cor. of secs. 24 and 25, with brass cap mkd.,