	Subdivision of T. 29 N., R. 47 E.
Chains	
7.20 22.85 23.10 25.00 26.90 29.40 40.00	Over rolling mountains. Mountain spur, slopes NE. 105 ft. above sec. cor. Ravine, course S. 180 ft. below spur. Road, bears N. and S. Spur of hill, slopes SE. 95 ft. above ravine. Road bears NW. and SE. Wash, course SE. Ascend E. slope 180 ft. to Set a basalt stone 14xllx5 ins., 9 ins. in the ground for \$\frac{1}{4}\$ sec. cor. marked \$\frac{1}{4}\$ on N. face, raise a mound of stone 2 ft. base, \$1\frac{1}{2}\$ ft. high, N. of cor. Whence a mining cabin bears N.30°52'W. 46.12 chs. dist. A mining cabin bears N.30°W., 43.06 chs. dist. A mining cabin bears N.31°16'W. 44.30 chs. dist. A mining cabin bears N.32°50'W., 46.88 chs. dist. A mining cabin bears N.35°30'W. 50.10 chs. dist. A deep shaft with a large dump bears N.45°28'W. 71.50
45.50 62.30 75.15 87.10 101.85 116.60	chs. dist. A shaft bears N.63°30'W., 47.10 chs. dist. Spur, slopes SE. 60 ft. above \$\frac{1}{4}\$ sec. cor. Ravine, course SE. Mountain spur, slopes NE. 165 ft. above ravine. Ravine, course NE. Mountain spur, slopes SW. 215 ft. above ravine. Descend W. slope of mountains, 230 ft. to Intersect the W. bdy. of the tp. at N.0°23'E. 9.63 chs. from the cor. of secs. 25 and 36. Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground for closing corner of secs. 30 and 31, with brass cap mkd: T 29 N R46E R47E S25 CC S36 S31 1914
	and raise a mound of stone 2 ft. base, $l\frac{1}{2}$ ft. high, E. of corner. Land; rolling mountains, with a general slope to the S. Soil; poor quality, coarse texture, contains much gravel and loose rocks. Quite dry 3rd rate. Fair growth sagebrush, not much grass, no timber. Much float and other mineral indications.
19.70 35.60 40.00	The sky was overcast with clouds at noon and it was impossible to take an observation for latitude. S.0°3'E. bet. secs. 31 and 32. Over rolling mountains. High mountain ridge, bears NW. and SE. 160 ft. above sec. cor. Descend S. slope. Wash, course SE. 340 ft. below ridge. Set an iron post 3 ft. long, l in. diam., 24 ins. in the ground for \(\frac{1}{4} \) sec. cor., with brass cap mkd: S 31\(\frac{1}{4} \) S32
48.60	and raise a mound of stone 2 ft. base, $l\frac{1}{2}$ ft. high, W. of corner. Ridge bears NW. and SE. Descend SW. slope 165 ft. to Intersect the S. Bdy. of the tp. at N.89°2'W. 4.93 chs. from the cor. of secs. 5 and 6. Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in