

Chains	N.0°22'W. bet. secs. 3 and 4. Over level land, with a slight slope to the SE.
20.25	Wash, course NE.
40.30	The $\frac{1}{4}$ sec. cor. I destroy all traces of this cor. and its accessories and reestablish it at the same point as follows: Set an iron post 3 ft. long, 1 in. diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd: S4 $\frac{1}{4}$ S3 1914
80.48	dig pits 18x18x12 ins. N. and S. of post 3 ft. dist., and raise a mound of earth 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. The cor. of secs. 3 and 4. Land, level, with a slight slope to the E. Soil: poor quality, fine texture, sandy loam; several feet in depth, contains too much alkali and other salts; 3rd rate. Scattering growth of greasewood and chico, 3rd rate. Nov. 17, 1914.
SUBDIVISIONS OF T.31 N., R. 48 EAST.	
Nov. 17, 1914.	
From the cor. of secs. 3, 4, 9 and 10, I run East between secs. 3 and 10. Over level land.	
15.05	Creek, 2 lks. wide, course NE.
40.00	Set an iron post 3 ft. long, 1 in. diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. of sec. 3, with brass cap mkd: S 3 $\frac{1}{4}$ 1914
79.47	dig pits 18x18x12 ins. E. and W. of post 3 ft. dist. and raise a mound of earth 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor. Set temp. cor. for SE. cor. of sec. 3. Land, level with a slight slope to the NE. Soil, poor quality, fine texture, sandy loam; several feet in depth. Contains too much alkali and other salts, 3rd rate. Scattering sagebrush and greasewood. No timber.
40.00	From the cor. of secs. 2, 3, 34 and 35, on the N. Bdy. of Tp., South bet. secs. 2 and 3. Over level land with a slight slope to the NE. Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for the $\frac{1}{4}$ sec. cor. for sec. 2, with brass cap mkd: S2 $\frac{1}{4}$ 1914
40.28	dig pits 18x18x12 ins. N. and S. of cor. 3 ft., dist., and raise a mound of earth 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor. Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for the $\frac{1}{4}$ sec. cor. for sec. 3, with brass cap mkd: S3 $\frac{1}{4}$ 1916
80.73	dig pits 18x18x12 ins. N. and S. of cor. 3 ft. dist., and raise a mound of earth 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. NOTE: On May 17, 1916, in accordance with Supplemental Special Instructions dated May 9, 1916; I set the above $\frac{1}{4}$ sec. cor. for sec. 3; and changed the markings on the $\frac{1}{4}$ sec. cor. for secs. 2 and 3, set by me Nov. 17, 1914, to markings for $\frac{1}{4}$ sec. cor. for sec. 2 only. Also changed the mound of earth from the W. to the E. side of the post. The temp. SE. cor. of sec. 3. Winfred A. Pray U.S. Surveyor. At this point, set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground for the SE. cor. of sec. 3, with brass cap mkd: T31N R48E S3 1914
	dig a a pit 36x36x12 ins. in the section N.W. of cor. 8 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high NW. of cor. Land, level with a slight slope to the NE. Soil, poor quality, fine texture, sandy loam, several