Chains

Thence I run
S. 89° 39'W. on a true line on the south bdy. of sec. 32, the course and distance of this $\frac{1}{2}$ mile by previous retrace-

Over slightly rolling valley land.

30.00 Wash, 15 lks. wide, course S.20°E. The old $\frac{1}{4}$ cor. of secs. 5 and 32, heretofore described, I 39.36

destroy all traces of the old cor. and reestablished the corner at the same point as follows: Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for 4 sec. cor., with brass cap marked

''S 5

and raise a mound of stone, 2 ft. base, $l_{\frac{1}{2}}$ ft. high S. of corner.

I now change bearing and run S. 89° 31'W. along the S.

bdy of sec. 32, course by previous retracement Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in 40.00 the ground for \(\frac{1}{4}\) sec. cor., with brass cap marked

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of corner.

68.80 Wash, 15 lks. wide, course S. 79.76

The old cor. of secs. 5, 6, 31 and 32, The last $\frac{1}{2}$ mile being within limits I here build a corner as follows: Set an iron post 3 ft. long, 3 ins. diam. 24 ins. in the ground for cor. of secs. 5, 6, 31 and 32, with brass cap marked

> T32N .R48E S 31 S 32 S 6 S 5 T31N R48E 1914

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of corner. Land, slightly rolling valley. Soil, sandy and gravelly, light clay loam, fine texture, rocky.

From the cor. of secs. 5, 6, 31 and 32 I run S. 89° 31'W. bet. secs. 6 and 31.

Over slightly rolling valley land, gradually ascending.

3.50

14.10

24.40

33.70

Wash, 20 lks. wide, course S. 30°E.

Wash, 10 lks. wide, course S. 10°E.

Wash, 10 lks. wide, course S. 10°E.

Wash, 20 lks. wide, course S. 10°E.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., with brass cap marked 40.00

 $\frac{5}{4}$

and raise, amound of, stone 2 ft. base, $l^{\frac{1}{2}}$ ft. high N. of corner.

The old $\frac{1}{4}$ cor. of secs. 6 and 31, I destroy all traces of the old cor, and reestablish at the same point as follows: