

Chains

bears N. 45°E. and S.45°W.
Land, mountainous. Soil, clay, slide rock and volcanic rock, barren outcropping ledges. Undergrowth, sage and desert brush, bunch grass. No timber.

- 40.00 S. 89° 51'E. on a random line bet. secs. 3 and 10.
Set temp. $\frac{1}{4}$ sec. cor.
- 80.23 Intersect N. and S. line, 5 lks. S. of the cor. of secs. 2, 3, 10 and 11
Thence I run
N. 89° 53'W. on a true line, bet. secs. 3 and 10.
Over mountainous land, descend.
- 1.20 Gulch, course N. 75° E.; ascend abruptly.
- 22.40 Top of abrupt ascent, ascend gradually.
- 25.70 Top of spur, 470 ft. above gulch, projects S.20°E.; descend.
- 32.60 Head of draw, 30 ft. below top of ridge, course S.15°E.; ascend.
- 40.11 $\frac{1}{2}$ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S 3
 $\frac{1}{4}$
S 10
1914

- and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high N. of corner.
- 60.20 Top of ridge, 200 ft. above head of draw, bears N.50°E. and S.50°W.; ascend gradually along S. slope 100 ft. to the sec. cor.
- 80.23 The cor. of secs. 3, 4, 9 and 10.
Land, rolling and mountainous. Soil, clay with slide rock, shale and volcanic rocks, outcropping ledges. Undergrowth, sage and desert brush, bunch grass. No timber.

July 28, 1914.

Surveyed by A.T.Harris.

July 29, 1914: For solar on this date see line bet. secs. 2 and 11.

Knowing that the line bet. secs. 3 and 4, will not close within limits, I run

N. 0° 01'W. bet. secs. 3 and 4.

Over mountainous land and broken land, descend along W. slope.

- 3.30 Descend abruptly along N.W. slope of high ridge.
- 30.35 Top of spur, projects N.45°W. and S.45°E., descend.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam. 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

S 4 $\frac{1}{4}$ | S 3
1914

- and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high W. of corner.
- 72.00 Bottom of gulch, 4.40 ft. below top of spur, course N.60°W.; descend along W. slope.
- 82.56 Intersect N. bdy. of the Tp. 1.29 chs. N. 89° 40'W. of the point for the cor. of secs. 33 and 34, afterwards reestablished with an iron post heretofore described. At point of intersection I build a corner as follows: Set an iron post 3 ft. long, 2 ins. dia., 14 ins. in the ground to solid rock in mound of stone for closing corner of secs. 3 and 4, with brass cap mkd: