

Chains

6. I here build a corner as follows:
Set an iron post 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock and in a mound of stone for the $\frac{1}{4}$ cor. of sec. 6, with brass cap marked

S 6 $\frac{1}{4}$

1915

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of corner.

March 20, 1915.

Boundaries of T. 32 N., R. 48 E.

Latitudes, departures and closing errors.

Line designated	True bearing	Dist.	Latitude		Departures	
			N.	S.	E.	W.
Subdivisions	N.0°29'W	80.06	80.06			.67
	S.89°45'E.	81.51		.35	81.51	
	N.0°49'W.	80.13	80.12			1.14
	N.0°20'W.	79.81	79.81			.46
	N.0°28'W.	39.11	39.11			.32
	N.0°02'E	40.13	40.13		.02	
	N.0°03'W.	79.22	79.22			.07
	N.0°15'E.	83.50	83.50		.35	
N. Boundary	N.89°40'W	314.96	1.86			314.96
	S.89°39'W.	80.43		.49		80.43
W. Boundary	S.0°09'E.	40.18		40.18	.11	
	S.0°02'E.	44.22		44.22	.02	
	South	40.21		40.21		
	S.0°04'E	40.01		40.01	.05	
	S.0°10'E.	40.12		40.12	.12	
	S.0°17'E.	39.90		39.90	.20	
	S.0°15'W.	39.49		39.49		.17
	S.0°40'W.	40.07		40.07		.47
	S.0°07'W.	40.10		40.10		.08
	S.0°05'W.	40.09		40.09		.06
	S.0°07'W.	40.14		40.14		.08
	S.0°09'W.	40.16		40.16		.10
S. Boundary	S.89°51'E.	35.17		.09	35.17	
	N.89°31'E.	40.49	.34		40.49	
	N.89°31'E.	40.40	.34		40.40	
	N.89°39'E.	40.25	.24		40.25	
	N.89°36'E.	40.08	.28		40.08	
	N.89°34'E.	39.83	.30		39.83	
	N.89°50'E.	79.88	.23		79.88	
Convergency						.50
Totals			485.60	485.62	398.48	399.51
			485.60	485.60		398.48
Error in Latitude			.00	.02		
Error in Departure						1.03