

6.

Subdivision of Fract. T. 33 N., R. 48 E.

Chains
 26.00 Telephone line bears N. 75°E. and S. 75°W.
 26.85 Telephone line bears N.75°E. and S.75°W.
 26.90 S.P.R.R.Co. right of way fence bears N.75°E. and S.75°W
 33.20 Wagon road, bears N.60°E. and S.60°W.
 36.70 Old R.R. grade, bears N.60°E. and S.60°W.
 38.66 Proportional distance. Set an iron post, 3 ft. long, 1 in. in dia., 24 ins. in the ground for $\frac{1}{4}$ cor. of secs. 32 and 33, with brass cap mkd.,

S32 $\frac{1}{4}$ | S33
 1914

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
 Thence ascend over hilly ground.
 58.50 Leave rolling ground enter hills, bears E. and W.
 77.32 Intersect the cor. of secs. 32 and 33 which is an iron post as described by the Surveyor General in Group No. 25.
 This corner is 215 ft. above $\frac{1}{4}$ sec. cor.
 Land; 1st $\frac{1}{2}$ mile level, next 20.00 chs. rolling and S. part hilly.
 Vegetation, along level land, willows, sweet clover, rye grass, and some wild grass. Sagebrush and scanty grass in hills and rolling ground.
 Soil; N. $\frac{1}{2}$ mile a deep sandy loam, S. $\frac{1}{2}$ mile a gravelly clay loam, with rocky and gravelly subsoil.
 Drainage to the N. and W.
 August 8, 1914.

SUBDIVISION OF FRACT. T. 33 N., R. 48 EAST

Surveyed by A.T.Harris:-
 Aug. 8: At 2h. p.m., l.m.t., I set off 40° 40' N. on the lat. arc; 16° 13' N. on the decl. arc and determine a meridian at the cor. of secs. 34 and 35,
 Thence I run
 N. on a true line bet. secs. 34 and 35; descend from top of ridge.
 4.00 Leave top of ridge, bears N.35°W. and S. 35° E.
 19.40 Spur, 260 ft. below ridge, slopes N.E.; descend.
 33.00 Draw, 325 ft. below spur, course N.80°E., ascend.
 36.20 Spur, 20 ft. above draw, slopes N.E.; descend.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 34, with brass cap mkd.,

S34 $\frac{1}{4}$
 1914

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of corner.
 47.50 Draw, 200 ft. below spur, course N.50°E.; ascend.
 55.00 Low ridge, 30 ft. above draw, bears E. and W., descend.
 69.80 Wash 15 lksl wide, 4 ft. deep, course N. 70°W.
 77.90 Intersect S. bdy. of sec. 27, 1.43 chs. S.89°48'W. of the cor. of secs. 26 and 27, At intersection I build a corner as follows:
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for closing corner of secs. 34 and 35, with brass cap mkd.,

