

## Chains

South on a retracement line bet. secs. 28 and 29.

40.00 Find no trace of the original  $\frac{1}{4}$  sec. cor. after diligent search.

80.00 Find no trace of the original cor. of secs. 28, 29, 32 and 33, after diligent search.

South on a retracement line bet. secs. 32 and 33.

40.00 Find no trace of the old original  $\frac{1}{4}$  sec. cor. after diligent search.

80.16 The original cor. of secs. 4, 5, 32 and 33, which is a partially decayed stake 3 ins. square, 12 ins. above the ground, in old mound of earth. No marks are legible, except the following pencil markings: "Sec. Cor. 4-5 32-33". I learn from property owners in the vicinity that this is recognized as the original corner point.

In order to fix the locus of this cor. I take the following bearings: A frame house about a mile distant bears S.10°10'W. The center of the Western Pacific R.R. water tank, in Beowawe bears S.40°39'W. The steel smoke stack on Power Plant bears S.55°20'W. The center of S.P. R.R. water tank bears S.67°07'W.

The measurement from the north of the four miles is 16 lks. excess or 80.04 chs. per mile.

From the reestablished cor. of secs. 21, 22, 27 and 28 heretofore described,

West on a retracement line bet. secs. 21 and 28, for distance only.

40.09 No trace of the original  $\frac{1}{4}$  sec. cor. can be found after diligent search.

80.18 No trace of the original cor. of secs. 20, 21, 28 and 29 can be found after diligent search.

Set a temp. sec. cor.