

Chains

raise a mound of earth 4 ft. base, 2 ft. high, W. of cor.

The original cor. of secs. 8, 9, 16 and 17, as described by U.S. Surveyor Pray was a stake 18 ins. long, 2 ins. diam., with traces of markings remaining and lying on the ground on an old mound of earth, all traces of which including accessories were destroyed by him, and corner as above described re-established at same point.

The corners set by Mr. Pray were removed.

From the restored cor. of secs. 11 and 14,
N.0°3'W. bet. secs. 10 and 11.

Over rolling mountainous land, through sagebrush and greasewoods, ascend gently.

18.00 Wash, 10 lks. wide, 1 ft. deep, course E.

22.00 Rolling ridge, or water shed, 30 ft. above sec. cor. bears NE. and SW.

39.00 Draw, 40 ft. below ridge, course W. Ascend.

40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in the ground for the $\frac{1}{4}$ sec. cor. for sec. 11 only, marked on brass cap:

| $\frac{1}{4}$ S11
1916

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

41.94 $\frac{1}{2}$ Later, At this point:

Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for the $\frac{1}{4}$ sec. cor. for sec. 10 only, marked on brass cap:

$\frac{1}{4}$ S10 |
1916

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

49.40 Top of ridge, 40 ft. above draw, bears N.60°E. and S.60°W.

Descend

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.